



## ASG4025-AL Specification Sheet

### Snow Guards

#### PART 1 – GENERAL

##### 1.1 SUMMARY

###### A. WORK INCLUDES

1. ASG4025 snow guard that does not penetrate roof using clamp to seam technology.
2. Coordinate with installation of roof to assure proper placement of snow guards.
3. Provide appropriate snow guard and fasteners for the roof system.

###### B. RELATED SECTIONS

1. Section 076000: Flashing and Sheet Metal	MasterFormat 2016 07 60 00
2. Section 073100: Shingles and Shakes	MasterFormat 2016 07 31 00
3. Section 073200: Roofing Tiles	MasterFormat 2016 07 32 00
4. Section 077253: Snow Guards	MasterFormat 2016 07 72 53

##### 1.2 SYSTEM DESCRIPTION

###### A. COMPONENTS

Bracket: Snow guard bracket with (3) set screws.

1. ASG4025-AL

###### B. ACCESSORIES

1. PP75, tubing
2. Couplings
  - a. PP84, external
  - b. PP86, internal
3. PP56, end caps
4. PP65, end collars
5. PP95, ice flags

###### C. DESIGN REQUIREMENTS

1. Spacing to be recommended by manufacturer or building engineer.
2. Install 3 set screws per snow guard.
3. It is important to design new structures or assess existing structures to make sure they can withstand retained snow loads.

##### 1.3 SUBMITTAL

- A. Submit manufacturer's specifications, standard detail drawings, installation instructions, and recommended layout.

##### 1.4 QUALITY ASSURANCE

- A. Installer to be experienced in installation of specified roofing material and snow guards for not less than 5 years in the area of the project.

##### 1.5 DELIVERY / STORAGE / HANDLING

- A. Inspect material upon delivery and order replacements for any missing or defective items. Keep material dry, covered and off the ground until installed.



## ASG4025-AL Specification Sheet

### Snow Guards

## PART 2 – PRODUCTS

### 2.1 MANUFACTURER

A. Alpine SnowGuards®, a Division of Vermont Slate & Copper Services, Inc.  
289 Harrel St., Morrisville, VT 05661 | 888-766-4273 | [www.alpinesnowguards.com](http://www.alpinesnowguards.com)

### 2.2 MATERIALS

A. ASG4025 - 6000 Series Aluminum

### 2.3 ACCESSORY MATERIALS

A. PP75, tubing (choose one)

1. 6000 Series Aluminum - 1" outside diameter and .120" wall thickness, extruded.
2. 304 Stainless Steel - same dimensions as aluminum, welded.

B. Couplings (choose one)

1. PP84, external and exposed coupling which can also serve as 5" long expansion mechanism.

a. 6000 Series Aluminum

2. PP86, internal and concealed coupling, 3" long.

a. 6000 Series Aluminum

b. 304 Stainless Steel

3. PP56, end caps - 304 Stainless Steel

4. PP65, end collars (choose one)

a. 6000 Series Aluminum

b. 304 Stainless Steel

5. PP95, ice flags, 3" wide x length, optional (choose one)

a. 6000 Series Aluminum

b. 304 Stainless Steel

### 2.4 FINISH (choose one)

A. Mill Finish – standard

B. Powder Coated – available at additional cost

## PART 3 – EXECUTION

### 3.1 EXAMINATION

A. Substrate

1. Inspect structure on which snow guard system is to be installed and verify it will withstand any additional loading that it may incur. Notify general contractor of any deficiencies before installing Alpine SnowGuards' products.

2. Verify roofing material has been installed correctly prior to installing snow guards.

### 3.2 INSTALLATION

A. Comply with architectural drawings and snow guard manufacturer's recommendations for location of system. Comply with manufacturer's written installation instructions for installation and layout.

Document Version 08.11.2021

07 72 53 Snow Guards