



PD41 and PD410F-CU Specification Sheet Snow Guards

Part 1 – GENERAL

1.1 SUMMARY

A. WORK INCLUDES

1. PD41 and PD410F-CU gusseted snow guards that hook over the head of the tile.
2. Coordinate with roof installation to assure proper placement of snow guards.

B. RELATED SECTIONS

| | |
|---|----------------------------|
| 1. Section 076000: Flashing and Sheet Metal | MasterFormat 2016 07 60 00 |
| 2. Section 073100: Shingles and Shakes | MasterFormat 2016 07 31 00 |
| 3. Section 073200: Roof Tiles | MasterFormat 2016 07 32 00 |
| 4. Section 077253: Snow Guards | MasterFormat 2016 07 72 53 |

1.2 SYSTEM DESCRIPTION

A. COMPONENTS

1. PD41 and PD410F-CU snow guard system consists of individual metal snow guards.

B. DESIGN REQUIREMENTS

1. Spacing to be recommended by manufacturer or building engineer.
2. It is important to design new structures or assess existing structures to make sure they can withstand retained snow loads.

1.3 SUBMITTAL

- A. Submit manufacturer's specifications, standard detail drawings, installation instructions, and recommended layout.

1.4 QUALITY ASSURANCE

- A. Installer to be experienced in installation of specified roofing material and snow guards for not less than 5 years in the area of the project.

1.5 DELIVERY / STORAGE / HANDLING

- A. Inspect material upon delivery and order replacements for any missing or defective items. Keep material dry, covered and off the ground until installed.



PD41 and PD410F-CU Specification Sheet Snow Guards

Part 2 – PRODUCTS

2.1 MANUFACTURER

A. Alpine SnowGuards®, a Division of Vermont Slate & Copper Services, Inc.
289 Harrel St., Morrisville, VT 05661 | 888-766-4273 | www.alpinesnowguards.com

2.2 MATERIALS

- A. Copper – Strap, cap and gusset are 16 oz copper. Fleur-de-lis embellishment with hook is *only* available in copper and both have a minimum material thickness of .040.
- B. Lead-Coated Copper – 16 oz lead-coated copper.
- C. Aluminum – .032 aluminum; hook is .040 aluminum.
- D. Freedom Gray™ – 16 oz tin-zinc coated copper.
- E. Rheinzink® – .8mm Rheinzink®.

2.3 FINISH (choose one)

- A. Mill Finish – standard.
- B. Powder Coated – available at additional cost.
(Not available for PD410F-CU)
- C. Kynar 500® pre-painted coil – aluminum only.
(Not available for PD410F-CU)

Part 3 – EXECUTION

3.1 EXAMINATION

A. SUBSTRATE

1. Inspect structure on which snow guard system is to be installed and verify it will withstand any additional loading it may incur. Notify general contractor of any deficiencies before installing Alpine SnowGuards' products.
2. Verify roofing material has been installed correctly prior to installing snow guards.

3.2 INSTALLATION

- A. Comply with architectural drawings and snow guard manufacturer's recommendations for location of system. Comply with manufacturer's written installation instructions for installation and layout.

Document Version 04.26.23
07 72 53 Snow Guards