



PP235 Ludowici Spanish (Aluminum) Snow Guard Specification Sheet

PART 1 – GENERAL

1.1 SUMMARY

A. WORK INCLUDES

1. PP235LS Snow guard that attaches directly to roof deck.
2. Coordinate with installation of roof to assure proper placement of snow guards.
3. Provide appropriate snow guard and fasteners for roof system

B. RELATED SECTIONS

1. Section 07600: Flashing and Sheet Metal. MasterFormat 2016 07 60 00
2. Section 07310: Shingles. MasterFormat 2016 07 31 00
3. Section 07320: Roofing Tiles. MasterFormat 2016 07 32 00
4. Section 07720: Snow Guards. MasterFormat 2016 07 72 00
5. Division 7: Thermal and Moisture Protection.

1.2 SYSTEM DESCRIPTION

A. COMPONENTS

1. PP235LS Snow guard system consists of snow guard bracket assembly and base tile.
2. Two bolts attach bracket to base plate.
3. PP75, tubing (Snow Fence)
4. Couplings.
 - a. PP84, external
 - b. PP86, internal
5. PP56, end caps
6. PP65, end collars
7. PP95, ice flags, optional
8. Fasteners
 - a. To be of metal compatible with snow guards.
 - b. Fasteners should be selected for compatibility with roof deck.
 - c. Fastener strength should exceed or be equal to that of snow guard system.

B. DESIGN REQUIREMENTS

1. Spacing to be recommended by manufacturer or building engineer.
2. Install a minimum of 3 fasteners per snow guard.
3. It is important to design new structures or assess existing structures to make sure they can withstand retained snow loads.

1.3 SUBMITTAL

- A. Submit manufacturer's specifications, standard detail drawings, installation instructions, and recommended layout.

1.4 QUALITY ASSURANCE

- A. Installer to be experienced in installation of specified roofing material and snow guards for not less than 5 years in the area of the project.

1.5 DELIVERY / STORAGE / HANDLING

- A. Inspect material upon delivery and order replacements for any missing or defective items. Keep material dry, covered and off the ground until installed.



PP235 Ludowici Spanish (Aluminum) Snow Guard Specification Sheet

PART 2 – PRODUCTS

2.1 MANUFACTURER

A. Alpine SnowGuards®, a Division of Vermont Slate & Copper Services, Inc.
289 Harrel St., Morrisville, VT 05661 | 888-766-4273 | www.alpinesnowguards.com

2.2 MATERIALS

- A. Snow Guard Bracket – 5000 Series Aluminum.
- B. Base Tile – 6000 Series Extruded Aluminum.
- C. Bolts – 304 Stainless Steel.
- D. PP75, tubing – 6000 Series Aluminum, 1" outside diameter and .120" wall thickness, extruded.
- E. PP84 and PP86, external and internal couplings (choose one)
 - 1. Aluminum – 6000 Series
 - a. Internal and concealed coupling 3" long.
 - b. External and exposed coupling which can also serve as a 5" long expansion mechanism.
- F. PP56, end caps – 304 Stainless Steel.
- G. PP65, end collars – 6000 Series Aluminum.
- H. PP95, ice flags, optional – 6000 Series Aluminum 3" wide x length.
- I. Fasteners (can be purchased from others) to be compatible with chosen roof application and meet specified pull-out values as shown in load test data.

2.3 FINISH (choose one)

- A. Mill Finish – standard
- B. Powder Coated – available at additional cost

PART 3 – EXECUTION

3.1 EXAMINATION

- A. Substrate
 - 1. Inspect structure on which snow guard system is to be installed and verify it will withstand any additional loading that it may incur. Notify general contractor of any deficiencies before installing Alpine SnowGuards' products.
 - 2. Verify that roofing material has been installed correctly prior to installing snow guards.

3.2 INSTALLATION

- A. Comply with architectural drawings and snow guard manufacturer's recommendations for location of system. Comply with manufacturer's written installation instructions for installation and layout.

Document Version 08.10.2021
07 72 53 Snow Guards